

## 1. Product Description

- **Dimensions** 1285 L x 186 LA x 8 H mm
- **Packaging** Box: 9 boards - 2,15 m<sup>2</sup> (15,3 kg)  
Pallet: 56 boxes - 120,46 m<sup>2</sup> (880 kg)
- **Composition**
  - > surface layer Paper impregnated with melamine resin
  - > Substrate Moisture-resistant High Density Fibreboard, HDF
  - > Backing Paper impregnated with melamine resin
- **Caractéristiques** WoodStructure
- **Installation** Glue-free mechanical locking system produced under licence of Välinge Innovation AB, Flooring Industries Ltd et Faus Group Inc
- **Instruction d'installation** See box inlay or [www.berryaloc.com](http://www.berryaloc.com)

## 2. Requirements

- **General requirements** According EN13329
- **Classification requirements** Class 23/32

Characteristics	Method	Requirement	Typical value
1. Abrasion resistance	EN 13329	AC4 (IP ≥ 4.000)	IP ≥ 4.000
2. Impact resistance	EN 13329	IC 2	IC 2
3. Resistance to staining	EN 438	5 (groups 1 + 2); 4 (group 3)	5 (groups 1 + 2); 4 (group 3)
4. Resistance to cigarette burns	EN 438	4	4
5. Effect of a furniture leg	EN 424	No damage (foot type 0)	No damage (foot type 0)
6. Effect of a castor chair	EN 425	No change in appearance or damage	No change in appearance or damage
7. Thickness swelling	EN 13329	≤ 18%	≤ 18%

## 3. CE - classification according EN14041

- **Fire resistance** C<sub>fl</sub>-S1
- **Formaldehyde** E1
- **Slipperiness** DS

## 4. Other technical data

- **Labelling according to French VOC emission regulation** A
- **Floor heating** See specific instructions at [www.berryaloc.com](http://www.berryaloc.com)
- **Thermal resistance in combination with underlay Excellence Endurance** 0,10 m<sup>2</sup> K/W

## 5. Warranty and maintenance

- **Residential warranty** 20 years
- **Warranty conditions** See [www.berryaloc.com](http://www.berryaloc.com)
- **Care and maintenance** See [www.berryaloc.com](http://www.berryaloc.com)